



# GX-2408T

## LUXURY SERIES

## Key Feature

- 200dpi/300dpi Print Resolution Selection
- Protect the top cover from falling
- Internally scalable true type font engine
- Firmware emulates TSPL, EPL, ZPL, ZPL II, DPL
- 400 MHz 32-bit ARM9 processor with 128 MB PSRAM, 128 MB Flash
- Internal Ethernet, RS-232, USB 2.0 , USB Host for scanner or PC keyboard
- Low Maintenance with Replaceable Auto-Cutter, Print Head and Platen Rollers



Transport



Warehousing



Manufacturing



Retail



Shelf labeling

# LUXURY SERIES

## 4 Inch Direct Thermal & Thermal Transfer Barcode Printer

MODEL	GX-2408T	GX-3406T
Level	Standard	Standard
Resolution	8dots/mm (203dpi)	12dots/mm (300dpi)
Max. Print Speed	203mm (8")/Second	152mm (6")/Second
Max. Print Width	104mm (4.09")	108.4mm (4.27")
Max. Print Length	25,400mm (1000")	11,430mm (450")
Memory RAM	128 MB PSRAM	128 MB PSRAM
Memory ROM	128 MB Flash	128 MB Flash
Printing Method	Thermal Transfer & Direct Thermal	
CPU	400 MHZ, 32 bit, ARM 9	
Printer language	Compatible to TSPL, EPL, ZPL, ZPL II, DPL	
Interface	<ul style="list-style-type: none"> <li>· RS-232</li> <li>· USB 2.0 High Speed 480Mbps</li> <li>· USB Host 2.0, for scanner or PC keyboard</li> <li>· Internal Ethernet 10/ 100Mbps</li> <li>· Internal Bluetooth 4.0 (Optional)</li> <li>· Internal WiFi (Optional)</li> </ul>	
Internal fonts	<ul style="list-style-type: none"> <li>· 8 alpha-numeric bitmap fonts</li> <li>· True type font engine (need download scalable font file)</li> </ul>	
Rotation	Font and barcode support 0, 90, 180, 270 degree	
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI	
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, MaxiCode, Aztec Code, Data Matrix	
Dealer Option	<ul style="list-style-type: none"> <li>· Cutter (Optional)</li> <li>· Peeler (Optional)</li> </ul>	
Power	<ul style="list-style-type: none"> <li>· Input: AC 100-240V, 50-60Hz.</li> <li>· Output: DC 24V, 2.5A, 60W</li> </ul>	
Physical Dimension	211mm(W) * 192.3mm(H) * 290.7mm(D)	
Net Weight	2.56kg	

### Certification

FCC Class A, CE Class A, CCC, BIS, CB

### Environment concern

Comply with RoHS, REACH, WEEE

### Accessories

- Windows Label Editing Software, Driver and Operator's Manual CD-ROM
- 1" ribbon spindle x 2 (for 300m ribbon)
- Quick Installation Guide
- External universal switching power supply
- Power Cord
- USB Cable

