

GP-M324

3 Inch Bluetooth Mobile Printer



Key Feature

- Max 60mm/s Print Speed
- 203 DPI High-Definition Printing Resolution
- Supports Printing Waybills and Labels
- Three buttons + OLED screen for quick setup
- Offers Type-C and Bluetooth for Quick Pairing
- Optional belt clip and strap for hands-free carrying
- Rated IP42 for water and dust resistance, withstands 1.2m drop tests



Long-Lasting Battery



Rugged and Durable



Flexible Connect

3 Inch Mobile Label Printer

MODEL	GP-M324
Printing Method	Direct Thermal
Printing Command	TSPL, CPCL
Resolution	203DPI
Printing Speed	60mm/s (MAX)
Printing Width	72mm
Print Head Temperature Detection	Thermistor
Print Head Position Detection	Microswitch
Paper Detection Sensor	Opposite Sensor, Reflective Sensor
Sensor Position	Left side
Display	128×64 OLED
Buttons	Power/Save, Feed/Setup, Menu
Communication Interface	USB+Bluetooth
USB Port Specification	Type-C
USB VID PID	VID: 0471 PID: 0055
Maximum Printing Size	72 mm × 300 mm
Graphics	Monochrome PCX, BMP image file printing
QR Code	QRCODE, PDF417
Character Set	Simplified Chinese (GB18030): 16*16, 20*20, 24*24 Traditional Chinese (BIG5): 24*24, Korean (KSC5601): 24*24
Character Magnification/Rotation	Horizontal and vertical magnification 1-10 times Rotation printing (0°, 90°, 180°, 270°)
Paper Type	Continuous paper, Label paper, Reverse black label paper
Medium Width	25-80mm
Paper Thickness	0.06mm-0.17mm
Paper Roll Outer Diameter	51mm
Paper Output Method	Top output
Power Supply	Input: DC 5V 1A
Charging Time	≤3h
Battery Standby Time	≥72h
Battery Printing Distance	≥200m (12.5% print density) (25°C)
Battery Cycle Life	400 times, ≥80%
Battery Capacity	7.4V/2000mAh
Net Weight	360g
Dimensions	114mm(W) * 112mm(D) * 60mm(H)



IOS



Android



Windows

Work Environment

- Temperature: 5-40°C
- Humidity: -20 ~ 55°C

Accessories

- Quick Installation Guide
- Lithium Battery
- Power Adapter
- USB Cable

Application Industries



Transport



Fine-Dining



Manufacturing



Retail



Traffic Enforcement