

GS-2408DM

4" Desktop Direct Thermal Label Printer



Key Features

- 203.2mm (8") per second print speed for 203 dpi.
- Internally scalable True type font engine.
- Firmware emulates the following: TSPL, ZPL, ZPL II.
- Provides Windows printer utility, Windows SDK, and Android SDK.
- Solutions for retail POS, shelf labeling, office applications, and shipping.

POWERFUL | HIGH PERFORMANCE | AFFORDABLE

SURPASS SERIES

4" Desktop Direct Thermal Label Printer

MODEL	GS-2408DM
Printing method	Direct Thermal
Resolution	8dots/mm(203DPI)
Print speed	203.2mm(8")/sec
Print width	104 mm(4.1")
Paper output	Front exit
Interface	Wi-Fi, Bluetooth, USB
Memory RAM	8 MB SDRAM
Memory ROM	16 MB Flash
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5
2D Barcode	QR Code, PDF417, Data Matrix
User Interface	1 power switch, 2 buttons (Feed & Pause) 2 LEDs (Online, Error)
Sensors	Head open sensor, Reflective sensor (moveable), Transmissive sensor (moveable)
Label roll capacity	127mm (5")OD
Printer language	Compatible to TSPL, ZPL, ZPL II
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)
Dimension	238mm (L) *180mm (W) *174.7mm (H)
Net weight	1.76kg



Environment concern

Comply with RoHS, REACH, WEEE

Certification

FCC, CE, CCC, BIS, CB

Application Industries



Healthcare



Shelf labeling



Large Retailer



Retail



Shipping



Shopping Mall