

GA-L330

LINERLESS PRINTER

3" Thermal Receipt Printer




KEY FEATURES


- Built for flexibility, it prints on linerless and continuous paper roll.
- Ideal for item tags, takeaway, shelf, package labels used in restaurant, retail store and warehouse.
- Front-exit design supports desktop or shelf installation for versatile applications.
- Work with paper width from 20 to 80mm, allow user variable length printing.
- Easy toolless replacement of TPH, platen roller and auto cutter.
- Users can print the pre-stored labels by simply pressing the printer's multifunction button.



Linerless Label



Normal Label



Linerless Printer

3" Thermal Receipt Printer

MODEL	GA-L330
Printing Method	Direct Thermal
Resolution	203DPI
Print Speed	160mm/sec
Print Width	72mm
Paper Width	79.5±0.5mm
Paper Output	Front Exit
Interface	USB 2.0 + RS-232 + Ethernet + RJ11 CashDrawer Wi-Fi (Optional) Bluetooth (Optional)
1D Barcode	CODE128 / EAN128 / ITF / CODE39 / CODE39C / CODE39S / CODE93 / EAN13 / EAN13+2 EAN13+5 / EAN8 / EAN8+2 / EAN8+5 / CODABAR / POSTNET / UPC-A/UPCA+2/UPCA+5 UPCE / UPCE+2 / UPCE+5 / MSI / MSIC / PLESSEY / ITF14 / EAN14
2D Barcode	QR Code, PDF417, Data Matrix
User Interface	1 Feed Switch 3 LEDs (Online, Error, Power)
Sensors	Head Open Sensor, Reflective Sensor (Moveable), Transmissive Sensor (Moveable)
Label Roll Capacity	105mm (4.13")OD
Emulation	Compatible to ESC/POS
Dimension	210mm (L) *142mm (W) *173mm (H)



Application Industries



Healthcare



Shelf labeling



Large Retailer



Retail



Shipping



Shopping Mall



Cost reduction

No liner, less storage and shipping;
30-40% more labels per roll, fewer changes.

Operation efficiency

Labels can be applied more quickly as
there is no need to peel label off its backing.



Environmentally-friendly

As labels come without backing paper,
there is less waste, resulting in reduced carbon emissions.