

GV-2408D

4" Desktop Direct Thermal Label Printer



Key Features

- 203 mm (8") per second print speed for 203 dpi.
- Internally scalable true type font engine.
- Firmware emulates the following: TSPL, ZPL, ZPL II.
- Provides Windows utility, Android utility, Windows SDK, Android SDK and iOS SDK.
- Solutions for retail POS, shelf labeling, office applications and logistic.

POWERFUL | HIGH PERFORMANCE | AFFORDABLE

4" Desktop Direct Thermal Label Printer



MODEL	GV-2408D
Printing method	Direct Thermal
Resolution	203DPI
Print speed	203mm(8")/second
Print width	104 mm(4.09")
Interface	· USB 2.0 · Ethernet 10/100Mbps · Internal Bluetooth 4.2 (Factory option) · Internal Wi-Fi (Factory option)
1D Barcode	Code 11, Code 39, Code 93, Code 128 (subsets A, B, C), UPC-A, UPC-E, UCC-128, Codabar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Pleassy, PostCode, Telepen
2D Barcode	QR Code, Micro QR Code, PDF417, Micro PDF417, MaxiCode, Aztec Code, Data Matrix
User Interface	1 power switch, 2 buttons (Feed & Pause) 2 LEDs (Online, Error)
Sensors	Head open sensor Reflective sensor (Moveable), Transmissive sensor
Label roll capacity	Max. 127mm (5")OD
Printer language	Compatible to TSPL, ZPL, ZPL II
Media type	Continuous, die-cut, black mark, fan-fold, notched (Outside wound)
Dimension	245mm (L) *186mm (W) *178mm (H)
Net weight	1.56kg
Certification	FCC, CE

Application Industries



Healthcare



Shelf labeling



E-commerce



Retail



Logistic



Shopping Mall